

PowerMust 600 / 800 LCD Line Int., Schuko or IEC

PM 600 / 800 LCD



Backside PM 600 / 800 LCD IEC



Backside PM 600 / 800 LCD Schuko

Features

- Line Interactive UPS
- Touch Screen LCD to display UPS information
- Compact size (30,0 x 10,1 x 14,2cm)
- Microprocessor control guarantees high reliability
- Discharge and overcharge protection
- Auto restart while AC is recovering
- Off mode charging
- Visual and audible Alarm system
- Cold start function

PowerMust 600 / 800 LCD Line Int., Schuko

Specification

MODEL	PowerMust 600 LCD	PowerMust 800 LCD
INPUT		
Capacity	600VA/360W	800VA/480W
Nominal Voltage	220/230/240VAC	
Voltage Range	162-290 VAC	
Frequency Range	50/60 Hz \pm 1 Hz (auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt. Mode)	220 / 230 /240 \pm 10%	
Frequency Range (Batt. Mode)	50 / 60 Hz \pm 1 Hz	
Transfer Time	Typical 2-6 ms	
Waveform (Batt. Mode)	Simulated Sine Wave	
Protection	Overload, discharge and overcharge protection	
BATTERY		
Battery Type	12 V / 7 AH x1	12 V / 9 AH x 1
Recharge Time	4 hours to 90% capacity	
Backup Time (at 100W load)	16 min.	20 min.
AUDIBLE ALARM		
Battery Mode	Sounding every 10 seconds	
Low Battery at battery mode	Sounding every second	
Fault	Continuously sounding	
Battery replacement	Sounding every 2 seconds	
Overload	Sounding every 0.5 second	
PHYSICAL		
Dimension, D x W x H (mm)	300 x 101 x 142	
Net Weight (kgs)	4,5	5,0
ENVIRONMENT		
Operation Humidity	0-90% RH @ 0-40 $^{\circ}$ C (non-condensing)	
Noise Level	Less than 40 dB	
INTERFACE		
Power Cord Connector	Schuko input powercord	
Outlet	Schuko 2 x or 4 x IEC	
Phoneline/ Network protection	RJ11	
USB port	Yes	
LED/LCD	LCD	
MANAGEMENT		
USB Port	Windows [®] 2000/2002/XP/Vista/2008/7/8/10, Linux and MAC	