

PowerMust 1500 Sinewave LCD Line Int., Schuko



PM 1500 Sinewave



PM 1500 Back side

Features

- Line Interactive UPS
- Pure Sinewave output
- LCD to display UPS information
- Compact size (39,7 x 14,6 x 20,5 cm)
- Microprocessor control guarantees high reliability
- Discharge, overcharge and overload protection
- Perfect power protection for mini servers & gaming PC's
- USB and RJ11/RJ45 protection
- Visual and audible Alarm system
- Boost and Buck AVR for Voltage stabilization

PowerMust 1500 Sinewave LCD Line Int., Schuko

Specification

| | |
|------------------------------------|--|
| MODEL | PowerMust 1500 Sinewave LCD |
| INPUT | |
| Capacity | 1500VA/1050W |
| Nominal Voltage | 220/230/240VAC |
| Voltage Range | 162-290 VAC |
| Frequency Range | 50/60 Hz \pm 1 Hz (auto sensing) |
| OUTPUT | |
| AC Voltage Regulation (Batt. Mode) | \pm 10% |
| Frequency Range (Batt. Mode) | 50 / 60 Hz \pm 1 Hz |
| Transfer Time | Typical 2-6 ms, 10ms max. |
| Waveform (Batt. Mode) | Pure Sinewave |
| Protection | Overload, discharge and overcharge protection |
| BATTERY | |
| Battery Type | 12 V / 9 AH x 2 |
| Recharge Time | 6 hours to 90% capacity |
| Backup Time (at 100W load) | 20 min. |
| AUDIBLE ALARM | |
| Battery Mode | Sounding every 10 seconds |
| Low Battery at battery mode | Sounding every second |
| Fault | Continuously sounding |
| Battery replacement | Sounding every 2 seconds |
| Overload | Sounding every 0.5 second |
| PHYSICAL | |
| Dimension, D x W x H (mm) | 397 x 146 x 205 |
| Net Weight (kgs) | 12,2 |
| ENVIRONMENT | |
| Operation Humidity | 0-90% RH @ 0-40° C (non-condensing) |
| Noise Level | Less than 40 dB |
| INTERFACE | |
| Power Cord Connector | Schuko input powercord |
| Outlet | Schuko 2 x and 2 x IEC |
| Phoneline/ Network protection | RJ11 |
| USB port | Yes |
| LED/LCD | LCD |
| MANAGEMENT | |
| USB Port | Windows® 2000/2002/XP/Vista/2008/7/8/10, Linux and MAC |